



2088

2077

2060 - 2061



2061



2060

2061 - 2078 (INOX)



2078 (INOX)



2076 (INOX)

2076 - 2078



2078



2076

### CARACTÉRISTIQUES

- > APPLICATION SUR FENÊTRES À AUVENT D'ALUMINIUM, DE FIBRE DE VERRE, DE BOIS ET DE PVC
- > FABRICATION D'ACIER POINÇONNÉ TRAITÉ CONTRE LA CORROSION OU D'ACIER INOXYDABLE
- > LE PLUS ROBUSTE SUR LE MARCHÉ
- > RAPIDE À INSTALLER
- > CHOIX DE DEUX HAUTEURS
- > TRÈS COMPACTE, ELLE SE FIXE DANS LA ZONE DE LA PENTURE DU CADRE ET DU VOLET
- > COMPRESSION ET HAUTEUR AJUSTABLES
- > UTILISE LES MÊMES VIS QUE LA PENTURE



plot ajustable  
adjustable pin



base en inox  
stainless base

### FEATURES

- > APPLICATION ON ALUMINIUM, FIBREGLASS, WOOD AND PVC AWNING WINDOWS
- > MADE OF PERFORATED STEEL PROTECTED AGAINST CORROSION, OR MADE OF STAINLESS STEEL
- > THE STURDIEST ON THE MARKET
- > QUICK TO INSTALL
- > TWO HEIGHTS AVAILABLE
- > VERY COMPACT, TO BE INSTALLED IN THE HINGE AREA OF THE SASH AND FRAME
- > ADJUSTABLE IN HEIGHT AND COMPRESSION
- > USES THE SAME SCREWS AS THE HINGE

## FICHES INTERMÉDIAIRES SNUBBERS